



Certificate No.: 8106-H1038

Applicant for Certification: Taconova Group AG, Neunbrunnenstrasse 40, CH- 8050 Zürich

from: 02.07.1981

In accordance with our regulation ZW101 „general terms and conditions of the SGWA certification body water“ the SGWA certify the following serial products:

Rubric: Mixing valves

Denomination: NovaMix Standard 70 / 40, NovaMix Standard 70 FR,
NovaMix Standard 70 FS

Types: NovaMix Standard 70 / 40, without check-valve
252.60XX.104, (XX = 02, 03, 04, 22, 23, 24);
NovaMix Standard 70 / 40, with check-valve
252.6002.330, 252,6003.330;
NovaMix Standard 70 FR, without check-valve
252.6042.104, 252.6043.104
252.6042.211 (60 °C mixing temperature is preset);
NovaMix Standard 70 FS, without check-valve
252.6003.107, 252.6004.107, 252.6022.107

DN: 15 ... 25 PN: - tmax= 90°C

Certification Standard: SGWA ZW 102/1 (07/15), ZW 102/2 (07/16),
UBA-Guideline, DIN 50930-6 (2001)

Validity: 31.10.2019

Notes / Conditions:


In the case of the thermostatic mixing valves, hygienic assessments have been carried out, for the components which come into contact with the drinking water, according to the KTW recommendations, UBA guidelines, the DVGW worksheet W 270 and DIN 50930-6 (edition 2001).

No tests were carried out on technical requirements, characteristics, functions and acoustics.

The applicant is entitled to offer the above mentioned products as certificated by the SGWA and to use the above SGWA-conformity mark (publication in the list of certificates water).

Swiss Gas and Water Industry Association

Certification body water


Javier Fernandez
Head

Rubric: Mixing valves
 Denomination: NovaMix Standard 70 / 40, NovaMix Standard 70 FR,
 NovaMix Standard 70 FS

Types	DN	PN	C°	Acoustic group	Losses	Content Index	Metrological class
NovaMix Standard 70/40, without check-valve							
252.6002.104	15	-	90			-	
252.6003.104	20	-	90			-	
252.6004.104	25	-	90			-	
252.6022.104	15	-	90			-	
252.6023.104	20	-	90			-	
252.6024.104	25	-	90			-	
NovaMix Standard 70/40, with check-valve							
252.6002.330	15	-	90			-	
252.6003.330	20	-	90			-	
NovaMix Standard 70 FR, without check-valve							
252.6042.104	15	-	90			-	
252.6043.104	20	-	90			-	
NovaMix Standard 70 FR, 60° C mixing temperature is preset, without check-valve							
252.6042.211	15	-	90			-	
NovaMix Standard 70 FS, without check-valve							
252.6003.107	20	-	90			-	
252.6004.107	25	-	90			-	
252.6022.107	15	-	90			-	

The last 3 digits may differ from those listed types depending on customer requirements (branding).

Accessories: check-valve types 296.5203.003 and 296.5204.003